

## Specifications for Spey tapered VersiLeaders

| Speed<br>Ip/s | Test<br>Lbs. | Length<br>Feet | Speed<br>Cm/s | Test<br>Kgs. | Length<br>M | Loop<br>Color |
|---------------|--------------|----------------|---------------|--------------|-------------|---------------|
| Flt           | 24           | 10 & 15        | Flt           | 10.8         | 3 & 4.6     | Olive         |
| 1.5           | 24           | 10 & 15        | 3.7           | 10.8         | 3 & 4.6     | Clear         |
| 2.6           | 24           | 10 & 15        | 6.6           | 10.8         | 3 & 4.6     | Green         |
| 3.9           | 24           | 10 & 15        | 9.9           | 10.8         | 3 & 4.6     | Red           |
| 5.6           | 24           | 10 & 15        | 14.2          | 10.8         | 3 & 4.6     | Blue          |
| 7.0           | 24           | 10 & 15        | 17.8          | 10.8         | 3 & 4.6     | Black         |

- Tapered leader for smooth turnover and ease of casting
- Ultra smooth welded loop for easy connection to fly line
- Super supple with no memory
- Color coded for instant recognition

For maximum knot strength and performance attach RIO-Max® Plus or Fluoroflex® tippet material to the front end of the VersiLeader.

RIO Products • 5050 South Yellowstone Highway, Idaho Falls, ID 83402 USA  
Tel. 208 524 7760 • Fax. 208 524 7763 • [www.rioproducts.com](http://www.rioproducts.com)  
[rio@rioproducts.com](mailto:rio@rioproducts.com) • Photo: © ?

Spey VersiLeader

7  
30884 24228

8

Made in USA